

View Online at <https://aerobasegroup.com/nsn/5930-01-290-1252>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Driptight and shock proof

Overall Length:

Between 0.828 inches and 0.890 inches

Overall Height:

2.730 inches

Overall Width:

Between 0.828 inches and 0.890 inches

Body Length:

0.688 inches

Body Width:

0.750 inches

Body Height:

2.620 inches

Case Material:

Metal

Actuator Length:

Between 0.684 inches and 0.704 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.090 inches and 0.110 inches

Actuator Width:

Between 0.684 inches and 0.704 inches

Actuator Color:

Black single actuator and black single actuator and black single actuator

Illuminated Actuator Color:

Red single actuator and red single actuator and red single actuator

Actuator Inscription:

Rvk/on/off single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Three-way split lens

Precious Material And Location:

Terminals gold

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0