

View Online at <https://aerobasegroup.com/nsn/5930-01-290-1252>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Driptight and shock proof

**Overall Length:**

Between 0.828 inches and 0.890 inches

**Overall Height:**

2.730 inches

**Overall Width:**

Between 0.828 inches and 0.890 inches

**Body Length:**

0.688 inches

**Body Width:**

0.750 inches

**Body Height:**

2.620 inches

**Case Material:**

Metal

**Actuator Length:**

Between 0.684 inches and 0.704 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.090 inches and 0.110 inches

**Actuator Width:**

Between 0.684 inches and 0.704 inches

**Actuator Color:**

Black single actuator and black single actuator and black single actuator

**Illuminated Actuator Color:**

Red single actuator and red single actuator and red single actuator

**Actuator Inscription:**

Rvk/on/off single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:**

Three-way split lens

**Precious Material And Location:**

Terminals gold

**Terminal Type And Quantity:**

3 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0