

View Online at <https://aerobasegroup.com/nsn/5930-01-290-1836>

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

3.320 inches

Outside Diameter:

0.250 inches single connection

Body Length:

1.370 inches

Overall Diameter:

1.090 inches

Pressure Switch Type:

Gage

Mounting Method:

Clamp

Contact Action Stimulus:

Increase

Proof Pressure:

300.00 pounds per square inch

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Criticality Code Justification:

Adaq and adav and abhp and cscf

Sensing Element Burst Pressure:

1000.00 pounds per square inch

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

5.0 amperes motor load second voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

32.00 actuation point pounds per square inch and 7.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

240.0 ac at sea level second voltage

Pressure Connector Type:

Shoulder, unthreaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0