

View Online at <https://aerobasegroup.com/nsn/5930-01-290-1841>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.020 inches

Overall Height:

0.920 inches

Overall Width:

0.920 inches

Body Width:

0.688 inches

Body Height:

0.688 inches

Case Material:

Metal

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.270 inches

Actuator Width:

0.620 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

Green single actuator and red single actuator

Actuator Inscription:

Monitor/two-way single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator red lower half of actuator green

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.680 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Horizontal split lens

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0