## NSN 5930-01-290-1914

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-290-1914 **Body Style:** Panel mount **Body Length:** 0.905 inches **Body Width:** 0.655 inches **Body Height:** 2.200 inches **Actuator Length:** 0.740 inches **Actuator Style:** Rectangular **Actuator Height:** 0.250 inches **Actuator Width:** 0.485 inches **Actuator Color:** White single actuator **Illuminated Actuator Color:** White single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.500 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac **Test Data Document:** 81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 9 tab, solder lug **Specification Data:** 81349-mil-s-22885/58 government specification Shelf Life: N/a

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5930-01-290-1914

Push Switch - Page 2 of 2



Fiig:

A053a0