# NSN 5930-01-290-4768

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-290-4768

# Thread Class:

2b single mounting facility

# Hazardous Locations/environmental Protection:

Corrosion resistant and shock resistant and vibration resistant

# Overall Length:

2.750 inches

# **Overall Height:**

2.500 inches

# **Overall Width:**

3.000 inches

# Individual Section Quantity:

2

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

## Mounting Facility Circle Radius:

## 1.156 inches single mounting facility

## **Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

## Thready Qty Per Inch (tpi):

24 single mounting facility

# Thread Size:

0.190 inches single mounting facility

## **Contact Voltage Rating In Volts:**

120.0 dc at sea level

## Mounting Facility Pattern:

Four position circular single mounting facility

## Switch Actuator Indexing Position Quantity:

2 single actuator

#### **Terminal Type:**

Tab w/screw

## **Contact Switching Action:**

Breaks before makes each section periphery

#### **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level

#### Style Designator:

Tap, circuit selector

#### **Thread Series Designator:**

Unc single mounting facility

# NSN 5930-01-290-4768

Rotary Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

