## NSN 5930-01-290-9512

Push Switch - Page 1 of 2



Thread Class:

2a

Body Style:

Bushing mounted

### **Overall Length:**

1.903 inches

#### **Overall Height:**

0.944 inches

#### **Overall Width:**

0.944 inches

#### Body Diameter:

Between 0.870 inches and 0.890 inches

#### **Bushing Length:**

Between 0.439 inches and 0.469 inches

#### **Body Length:**

Between 0.781 inches and 0.811 inches

#### Actuator Diameter:

Between 0.307 inches and 0.317 inches

#### Actuator Height:

Between 0.253 inches and 0.293 inches

#### Maximum Voltage Rating In Volts:

115.0 ac

Inclosure Type:

Fully enclosed

#### Mounting Method:

Threaded bushing

#### Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.469 inches

#### Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

#### **Precious Material And Location:**

Contacts silver

#### **Thread Series Designator:**

Uns

#### Terminal Type And Quantity:

2 tab, solder lug

#### Shelf Life:

N/a



# NSN 5930-01-290-9512

Push Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

