

View Online at <https://aerobasegroup.com/nsn/5930-01-291-0785>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

0.740 inches

**Overall Height:**

1.779 inches

**Overall Width:**

1.000 inches

**Unthreaded Mounting Hole Diameter:**

0.132 inches

**Distance Between Mounting Facility Centers:**

1.286 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

120.0 degrees celsius

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Quick disconnect, male

**Contact Load Current Rating:**

20.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+0.05/+0.75 actuation point inches of water and +0.05/+0.75 deactuation point inches of water

**Contact Adjustment Type:**

Internal actuation point screw and internal deactuation point screw

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Pressure Connector Type:**

Tapered, butt weld single connection

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Contact and terminal surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0