

View Online at <https://aerobasegroup.com/nsn/5930-01-291-0785>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.740 inches

Overall Height:

1.779 inches

Overall Width:

1.000 inches

Unthreaded Mounting Hole Diameter:

0.132 inches

Distance Between Mounting Facility Centers:

1.286 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

120.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

20.0 milliamperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.05/+0.75 actuation point inches of water and +0.05/+0.75 deactuation point inches of water

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Pressure Connector Type:

Tapered, butt weld single connection

Media For Which Designed:

Gas

Precious Material And Location:

Contact and terminal surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0