NSN 5930-01-291-0793

Push Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-01-291-0793
Thread Class:
2a
Body Style:
Bushing mounted
Overall Length:
1.903 inches
Overall Height:
0.944 inches
Overall Width:
0.944 inches
Body Diameter:
Between 0.870 inches and 0.890 inches
Bushing Length:
Between 0.439 inches and 0.469 inches
Body Length:
Between 0.781 inches and 0.811 inches
Actuator Diameter:
Between 0.307 inches and 0.317 inches
Actuator Height:
Between 0.253 inches and 0.293 inches
Maximum Voltage Rating In Volts:
maximum voltago rating in volto.
115.0 ac
115.0 ac
115.0 ac Inclosure Type:
115.0 ac Inclosure Type: Fully enclosed
115.0 ac Inclosure Type: Fully enclosed Mounting Method:
115.0 ac Inclosure Type: Fully enclosed Mounting Method: Threaded bushing
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi):
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size:
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement:
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, double break, momentary action single switch unit
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, double break, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage:
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, double break, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, double break, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Precious Material And Location:
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, double break, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Precious Material And Location: Contacts silver
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, double break, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Precious Material And Location: Contacts silver Thread Series Designator:
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, double break, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Precious Material And Location: Contacts silver Thread Series Designator: Uns

N/a

NSN 5930-01-291-0793

Push Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0