## NSN 5930-01-291-2806

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-291-2806

Body Style:					
Hole mounted					
Overall Length:					
1.380 inches					
Center To Center Distance Between Mounting Facilities Parallel To Length:					
1.125 inches					
Overall Height:					
0.504 inches					
Overall Width:					
0.546 inches					
Body Length:					
0.875 inches					
Body Width:					
0.460 inches					
Body Height:					
0.464 inches					
Case Material:					
Metal					
Unthreaded Mounting Hole Diameter:					
Between 0.136 inches and 0.140 inches					
Actuator Length:					
0.468 inches					
Actuator Height:					
0.040 inches					
Actuator Width:					
0.220 inches					
Actuator Position-action Relationship:					
Left position maintained and right position maintained					
Actuator Color:					
Black single actuator					
Maximum Voltage Rating In Volts:					
125.0 ac					
End Application:					
5895-01-259-1098 receiver, radio r-2368/urr					
Mounting Method:					
Unthreaded hole					
Nonpile-up Contact Arrangement:					
2 pole, double throw, both positions maintained single switch unit					
Contact Load Current Rating At Maximum Rated Voltage:					
4.000 amperes resistive ac					

Special Features:

Screwdriver slot actuator

## NSN 5930-01-291-2806

Slide Switch - Page 2 of 2



Draai	aua N	// neari	ial And	d Location:
rieci	ous n	nateri	ıaı Aliu	a Localion.

Contact surfaces and terminal surfaces silver

**Terminal Type And Quantity:** 

6 tab, solder lug

,

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0