NSN 5930-01-291-2806

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-291-2806

Body Style:
Hole mounted
Overall Length:
1.380 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.125 inches
Overall Height:
0.504 inches
Overall Width:
0.546 inches
Body Length:
0.875 inches
Body Width:
0.460 inches
Body Height:
0.464 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
Between 0.136 inches and 0.140 inches
Actuator Length:
0.468 inches
Actuator Height:
0.040 inches
Actuator Width:
0.220 inches
Actuator Position-action Relationship:
Left position maintained and right position maintained
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
125.0 ac
End Application:
5895-01-259-1098 receiver, radio r-2368/urr
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive ac

Special Features:

Screwdriver slot actuator

NSN 5930-01-291-2806

Slide Switch - Page 2 of 2



Draai	aua N	latari:	1 A n d	Location:
rieci	ous IV	าสเษาเ	ai Aiiu	Location.

Contact surfaces and terminal surfaces silver

Terminal Type And Quantity:

6 tab, solder lug

,

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0