NSN 5930-01-291-2807

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-291-2807

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and corrosion resistant

Overall Length:

4.880 inches

Overall Height:

1.780 inches

Overall Width:

1.650 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.040 inches

Actuator Roller Diameter:

0.440 inches

Housing Height:

1.780 inches

Housing Length:

2.840 inches

Housing Width:

1.650 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.342 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thread Size:

0.190 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action single switch unit

Switch Actuating Force:

64.0 ounces

Actuator Movement:

0.040 pretravel inches and 0.240 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

50.000 milliamperes resistive dc and 0.750 amperes resistive ac

NSN 5930-01-291-2807

Sensitive Switch - Page 2 of 2

Thread Series Designator:

Unf

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

