NSN 5930-01-291-2807

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-291-2807

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight and corrosion resistant
Overall Length:
4.880 inches
Overall Height:
1.780 inches
Overall Width:
1.650 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
2.040 inches
Actuator Roller Diameter:
0.440 inches
Housing Height:
1.780 inches
Housing Length:
2.840 inches
Housing Width:
1.650 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.342 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
440.0 ac and 230.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Thread Size:
0.190 inches
Nonpile-up Contact Arrangement:
2 pole, single throw, normally open, momentary action single switch unit
Switch Actuating Force:
64.0 ounces
Actuator Movement:

Contact Load Current Rating At Maximum Rated Voltage: 50.000 milliamperes resistive dc and 0.750 amperes resistive ac

0.040 pretravel inches and 0.240 overtravel inches and 0.020 differential inches

NSN 5930-01-291-2807 Sensitive Switch - Page 2 of 2



Thread Series Designator:
Unf
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0