

View Online at <https://aerobasegroup.com/nsn/5930-01-291-4449>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

2.720 inches

Overall Height:

0.800 inches

Overall Width:

0.800 inches

Body Width:

0.800 inches

Body Height:

0.800 inches

Actuator Length:

0.684 inches

Actuator Style:

Rectangular

Actuator Height:

0.070 inches

Actuator Width:

0.684 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Blue single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.650 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

Special Features:

Full display lens

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Terminal Type And Quantity:

11 tab, solder lug

Specification Data:

81349-mil-s-22885/56 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0