

View Online at <https://aerobasegroup.com/nsn/5930-01-291-4885>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture proof

Overall Height:

0.688 inches

Overall Width:

0.688 inches

Body Diameter:

0.562 inches

Bushing Length:

0.312 inches

Body Length:

0.712 inches

Case Material:

Metal

Actuator Diameter:

0.370 inches

Actuator Height:

0.250 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0