NSN 5930-01-291-6360

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-291-6360
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Fungus resistant
Overall Length:
Between 0.490 inches and 0.510 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.186 inches and 0.190 inches
Overall Height:
0.520 inches
Overall Width:
Between 0.190 inches and 0.210 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.190 inches and 0.210 inches
Body Height:
Between 0.340 inches and 0.360 inches
Unthreaded Mounting Hole Diameter:
Between 0.087 inches and 0.090 inches
Actuator Style:
Round
Actuator Diameter:
0.063 inches
Actuator Height:
0.050 inches
Actuator Free Position Height:
0.340 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.001 differential inches

NSN 5930-01-291-6360

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:	
100.000 milliamperes resistive dc	
Terminal Type And Quantity:	
3 turret	
Shelf Life:	
N/a	
Unit Of Measure:	

Demilitarization:

No

Fiig:

A053a0