

View Online at <https://aerobasegroup.com/nsn/5930-01-291-6885>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Moisture resistant and salt spray resistant and vibration resistant

**Bushing Length:**

0.300 inches

**Body Length:**

0.855 inches

**Body Width:**

0.510 inches

**Body Height:**

0.527 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.115 inches

**Actuator Height:**

0.410 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position momentary

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.682 inches

**Inclosure Type:**

Fully enclosed

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Test Data Document:**

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

12 tab, solder lug

**Specification Data:**

81349-mil-s-83731/21 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0