## NSN 5930-01-292-2360

Lock Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-292-2360

#### **Body Style:**

Bushing mounted

#### **Overall Length:**

2.219 inches

## **Overall Height:**

4.391 inches

## **Overall Width:**

2.219 inches

#### Bushing Length:

1.203 inches

**Body Length:** 

## 2.047 inches

Body Width:

#### 2.219 inches

**Body Height:** 

#### 2.219 inches

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

#### End Application:

Landing control an/mpn-14k

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Threaded bushing

#### Nonpile-up Contact Arrangement:

4 two circuit, double break/double make, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes resistive ac

#### **Special Features:**

Legend plate reads: safe, run

#### **Precious Material And Location:**

Contacts gold

#### **Terminal Type And Quantity:**

16 tab, solder lug or 16 quick disconnect, male

#### **Specification Data:**

24930-g330256 manufacturers specification control

Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

# NSN 5930-01-292-2360

Lock Switch - Page 2 of 2

**Fiig:** A053a0

