NSN 5930-01-292-2360

Lock Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-292-2360 **Body Style: Bushing mounted Overall Length:** 2.219 inches **Overall Height:** 4.391 inches **Overall Width:** 2.219 inches **Bushing Length:** 1.203 inches **Body Length:** 2.047 inches **Body Width:** 2.219 inches **Body Height:** 2.219 inches **Maximum Voltage Rating In Volts:** 125.0 ac and 28.0 dc **End Application:** Landing control an/mpn-14k Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing **Nonpile-up Contact Arrangement:** 4 two circuit, double break/double make, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 1.000 amperes resistive dc and 0.500 amperes resistive ac **Special Features:** Legend plate reads: safe, run **Precious Material And Location:** Contacts gold **Terminal Type And Quantity:** 16 tab, solder lug or 16 quick disconnect, male **Specification Data:** 24930-g330256 manufacturers specification control Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5930-01-292-2360

Lock Switch - Page 2 of 2



Fiig:

A053a0