

View Online at <https://aerobasegroup.com/nsn/5930-01-292-5870>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

0.420 inches

Overall Height:

1.325 inches

Overall Width:

0.420 inches

Bushing Length:

0.240 inches

Body Length:

0.320 inches

Body Width:

0.206 inches

Body Height:

0.400 inches

Actuator Style:

Round

Actuator Diameter:

0.196 inches

Actuator Height:

0.575 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc

Precious Material And Location:

Contact and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0