

View Online at <https://aerobasegroup.com/nsn/5930-01-292-7914>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and corrosion resistant

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Height:

0.920 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.320 inches

Housing Height:

1.780 inches

Housing Length:

3.740 inches

Housing Width:

1.650 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.342 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thread Size:

0.190 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action single switch unit

Switch Actuating Force:

32.0 ounces

Actuator Movement:

10.0 pretravel degrees and 40.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

50.000 milliamperes resistive dc and 0.750 amperes resistive ac

Thread Series Designator:

Unf

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0