

View Online at <https://aerobasegroup.com/nsn/5930-01-292-7914>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight and corrosion resistant

**Actuator Length:**

1.500 inches

**Actuator Style:**

Roller arm

**Actuator Height:**

0.920 inches

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.320 inches

**Housing Height:**

1.780 inches

**Housing Length:**

3.740 inches

**Housing Width:**

1.650 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.342 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.156 inches

**Maximum Voltage Rating In Volts:**

440.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Thread Size:**

0.190 inches

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally closed, momentary action single switch unit

**Switch Actuating Force:**

32.0 ounces

**Actuator Movement:**

10.0 pretravel degrees and 40.0 overtravel degrees and 4.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

50.000 milliamperes resistive dc and 0.750 amperes resistive ac

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0