

View Online at <https://aerobasegroup.com/nsn/5930-01-293-4013>

Inside Diameter:

0.250 inches all connections

Overall Length:

9.500 inches

Overall Height:

2.660 inches

Overall Width:

3.590 inches

Body Length:

3.470 inches

Body Height:

2.660 inches

Unthreaded Mounting Hole Diameter:

0.270 inches

Longest Horizontal Distance Between Mounting Centers:

2.720 inches

Longest Vertical Distance Between Mounting Centers:

2.720 inches

Pressure Switch Type:

Differential

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

600.00 pounds per square inch

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

6.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+150.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

70.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

600.0 ac at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0