NSN 5930-01-293-4610

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-293-4610	
Body Style:	
Panel mounted	
Hazardous Locations/environmental Protection:	
Explosion proof and humidity resistant	
Overall Length:	
3.050 inches	
Overall Height:	
0.750 inches	
Overall Width:	
0.750 inches	
Body Width:	
0.750 inches	
Body Height:	
0.750 inches	
Case Material:	
Metal	
Actuator Length:	
0.620 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.100 inches	
Actuator Width:	
0.620 inches	
Illuminated Actuator Color:	
Natural single actuator	
Actuator Inscription:	
Achvd single actuator	
Maximum Voltage Rating In Volts:	
115.0 ac and 28.0 dc	
Mounting Surface To Terminal End Distance:	
2.950 inches	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Panel	
Features Provided:	
Full display lens	
Nonpile-up Contact Arrangement:	
4 pole, double throw, one position momentary single switch unit	
Contact Load Current Rating At Maximum Rated Voltage:	

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-293-4610

Push Switch - Page 2 of 2



Precious Material And Location:
Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0