

View Online at <https://aerobasegroup.com/nsn/5930-01-293-7548>

**Body Style:**

Hole mounted

**Overall Length:**

Between 2.730 inches and 2.790 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Overall Height:**

1.907 inches

**Overall Width:**

Between 0.660 inches and 0.720 inches

**Body Length:**

Between 1.915 inches and 1.935 inches

**Body Width:**

Between 0.660 inches and 0.720 inches

**Body Height:**

Between 1.110 inches and 1.170 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.143 inches

**Actuator Length:**

Between 1.880 inches and 1.940 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

Between 1.177 inches and 1.197 inches

**Actuator Roller Diameter:**

Between 0.350 inches and 0.410 inches

**Actuator Roller Width:**

Between 0.160 inches and 0.220 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 125.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

0.5 ounces

**Switch Actuating Force:**

0.5 ounces

**Actuator Movement:**

Between 0.312 pretravel inches and 0.156 overtravel inches and 0.045 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0