

View Online at <https://aerobasegroup.com/nsn/5930-01-293-7548>

Body Style:

Hole mounted

Overall Length:

Between 2.730 inches and 2.790 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Overall Height:

1.907 inches

Overall Width:

Between 0.660 inches and 0.720 inches

Body Length:

Between 1.915 inches and 1.935 inches

Body Width:

Between 0.660 inches and 0.720 inches

Body Height:

Between 1.110 inches and 1.170 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.143 inches

Actuator Length:

Between 1.880 inches and 1.940 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 1.177 inches and 1.197 inches

Actuator Roller Diameter:

Between 0.350 inches and 0.410 inches

Actuator Roller Width:

Between 0.160 inches and 0.220 inches

Maximum Voltage Rating In Volts:

250.0 ac and 125.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

0.5 ounces

Actuator Movement:

Between 0.312 pretravel inches and 0.156 overtravel inches and 0.045 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 15.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0