NSN 5930-01-293-7550

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-293-7550

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.500 inches
Overall Height:
1.312 inches
Overall Width:
1.212 inches
Body Width:
1.212 inches
Body Height:
1.312 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Red single actuator and white single actuator
Actuator Inscription:
Vrbl plug/erase single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.400 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

NSN 5930-01-293-7550

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

inductive ac and 1.000 amperes lamp ac
Special Features:
Switch guard
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
1 socket, integrated wire termination
Shelf Life:
N/a
Unit Of Measure:
<u></u>

No

Demilitarization:

Fiig:

A053a0