

View Online at <https://aerobasegroup.com/nsn/5930-01-293-8356>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

2.562 inches

Outside Diameter:

0.250 inches single connection

Overall Height:

4.062 inches

Overall Width:

1.469 inches

Mounting Slot Width:

0.140 inches

Distance Between Mounting Facility Centers:

1.750 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -18.0 degrees celsius and 70.0 degrees celsius

Mounting Method:

Bracket and slot

Contact Action Stimulus:

Increase

Proof Pressure:

230.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+3.00/+30.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0