

View Online at <https://aerobasegroup.com/nsn/5930-01-294-2281>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Fungus resistant and humidity resistant and shock resistant

Overall Length:

Between 2.000 inches and 2.120 inches

Overall Height:

Between 0.740 inches and 0.760 inches

Overall Width:

Between 0.740 inches and 0.760 inches

Body Diameter:

Between 0.552 inches and 0.572 inches

Bushing Length:

Between 0.415 inches and 0.435 inches

Body Length:

Between 1.010 inches and 1.070 inches

Actuator Length:

Between 0.740 inches and 0.760 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.485 inches and 0.525 inches

Actuator Width:

Between 0.740 inches and 0.760 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Black single actuator

Actuator Inscription:

Time shift single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 7.000 amperes resistive ac and 3.000 amperes inductive ac

Special Features:

Actuator inscription characters are white when unilluminated and light red when illuminated

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret and 2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0