

View Online at <https://aerobasegroup.com/nsn/5930-01-294-2288>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Fungus resistant and humidity resistant and shock resistant

**Overall Length:**

Between 2.000 inches and 2.120 inches

**Overall Height:**

Between 0.740 inches and 0.760 inches

**Overall Width:**

Between 0.740 inches and 0.760 inches

**Body Diameter:**

Between 0.552 inches and 0.572 inches

**Bushing Length:**

Between 0.415 inches and 0.435 inches

**Body Length:**

Between 1.010 inches and 1.070 inches

**Actuator Length:**

Between 0.740 inches and 0.760 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.485 inches and 0.525 inches

**Actuator Width:**

Between 0.740 inches and 0.760 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Black single actuator

**Actuator Inscription:**

V with center dot single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 3.000 amperes inductive dc and 7.000 amperes resistive ac and 3.000 amperes inductive ac

**Special Features:**

Actuator inscription characters are white when unilluminated and light red when illuminated

**Precious Material And Location:**

Contact surfaces gold and contacts silver

**Unable To Decode:**

Unable to decode and unable to decode

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 turret and 2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0