

View Online at <https://aerobasegroup.com/nsn/5930-01-294-5784>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant and watertight

Overall Length:

2.405 inches

Overall Height:

0.875 inches

Overall Width:

0.950 inches

Bushing Length:

Between 0.595 inches and 0.655 inches

Body Width:

0.950 inches

Body Height:

0.875 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.245 inches and 0.255 inches

Actuator Height:

Between 0.245 inches and 0.255 inches

Actuator Free Position Height:

Between 0.845 inches and 0.905 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0