

View Online at <https://aerobasegroup.com/nsn/5930-01-294-7621>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Driptight and moisture proof and moisture resistant

Body Length:

0.740 inches

Body Width:

0.740 inches

Actuator Length:

0.990 inches

Actuator Style:

Rectangular

Actuator Width:

0.740 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

White single actuator and white single actuator

Actuator Inscription:

Open/close single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Weapon systems-arleigh burke class ddg; spruance class dd (963); vertical launching system, mk-41; ticonderoga class cg (47)

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc

Special Features:

Horizontally split screen

Precious Material And Location:

Contacts silver and contact surfaces gold

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

18 pin

Reference Number Differentiating Characteristics:

Differentiated by extra long reference number

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0