NSN 5930-01-294-9545

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-294-9545

| Body Style: | | | | | |
|---|--|--|--|--|--|
| Hole mounted | | | | | |
| Overall Length: | | | | | |
| 1.000 inches | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | | | |
| 0.812 inches | | | | | |
| Overall Height: | | | | | |
| 0.730 inches | | | | | |
| Overall Width: | | | | | |
| 0.500 inches | | | | | |
| Body Length: | | | | | |
| 0.650 inches | | | | | |
| Body Width: | | | | | |
| 0.500 inches | | | | | |
| Body Height: | | | | | |
| 0.290 inches | | | | | |
| Unthreaded Mounting Hole Diameter: | | | | | |
| 0.100 inches | | | | | |
| Actuator Length: | | | | | |
| 0.200 inches | | | | | |
| Actuator Height: | | | | | |
| 0.200 inches | | | | | |
| Actuator Width: | | | | | |
| 0.125 inches | | | | | |
| Actuator Position-action Relationship: | | | | | |
| Left position maintained and right position maintained | | | | | |
| Actuator Color: | | | | | |
| Black single actuator | | | | | |
| Maximum Voltage Rating In Volts: | | | | | |
| 28.0 dc and 250.0 ac | | | | | |
| End Application: | | | | | |
| 6625-01-212-3679 | | | | | |
| Mounting Method: | | | | | |
| Unthreaded hole | | | | | |
| Nonpile-up Contact Arrangement: | | | | | |
| 2 pole, double throw, both positions maintained single switch unit | | | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | | | |

Precious Material And Location:

Contact and terminal surfaces silver

500.000 milliamperes resistive dc and 2.000 amperes resistive ac

Terminal Type And Quantity:

6 tab, solder lug

NSN 5930-01-294-9545

Slide Switch - Page 2 of 2



| _ | | | - | | |
|---|----|----|---|------|---|
| C | hο | 14 | | .ife | • |
| • | | | _ | .116 | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0