

View Online at <https://aerobasegroup.com/nsn/5930-01-295-0181>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.843 inches

Shaft Diameter:

0.124 inches single actuator and 0.125 inches single actuator

Shaft Length:

0.281 inches single actuator

Overall Diameter:

1.344 inches

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Dummy terminal

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Clip

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0