

View Online at <https://aerobasegroup.com/nsn/5930-01-295-0182>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

Between 2.610 inches and 2.650 inches

Overall Height:

Between 2.610 inches and 2.770 inches

Overall Width:

Between 1.420 inches and 1.460 inches

Bushing Length:

Between 0.860 inches and 0.900 inches

Body Length:

Between 1.980 inches and 2.020 inches

Body Width:

Between 1.420 inches and 1.460 inches

Body Height:

Between 1.307 inches and 1.317 inches

Actuator Style:

Round

Actuator Height:

0.400 inches

Actuator Position-action Relationship:

Left position maintained and right position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

24 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

72 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0