

View Online at <https://aerobasegroup.com/nsn/5930-01-295-0182>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Shock resistant

**Overall Length:**

Between 2.610 inches and 2.650 inches

**Overall Height:**

Between 2.610 inches and 2.770 inches

**Overall Width:**

Between 1.420 inches and 1.460 inches

**Bushing Length:**

Between 0.860 inches and 0.900 inches

**Body Length:**

Between 1.980 inches and 2.020 inches

**Body Width:**

Between 1.420 inches and 1.460 inches

**Body Height:**

Between 1.307 inches and 1.317 inches

**Actuator Style:**

Round

**Actuator Height:**

0.400 inches

**Actuator Position-action Relationship:**

Left position maintained and right position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

24 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 3.000 amperes resistive ac

**Precious Material And Location:**

Terminal surfaces and contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

72 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0