

View Online at <https://aerobasegroup.com/nsn/5930-01-295-0913>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.359 inches single mounting facility and 0.391 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Moisture resistant and shock resistant and vibration resistant

**Overall Length:**

Between 3.238 inches and 3.396 inches

**Overall Height:**

0.700 inches

**Overall Width:**

Between 0.469 inches and 0.531 inches

**Shaft Diameter:**

0.249 inches 1st actuator and 0.251 inches 1st actuator

**Shaft Length:**

0.441 inches 1st actuator and 0.493 inches 1st actuator

**Individual Section Quantity:**

2

**End Application:**

Radar set an/aps-13 (v) 2

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section periphery

**Throw Quantity:**

2 each section periphery

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 all actuators

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Wire loop

**Contact Switching Action:**

Makes before breaks each section periphery

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Special Features:**

Four potentiometer sections

**Style Designator:**

Rectangular panel mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0