

View Online at <https://aerobasegroup.com/nsn/5930-01-295-2265>

**Outside Diameter:**

0.200 inches all connections

**Unthreaded Mounting Hole Diameter:**

Between 0.101 inches and 0.107 inches

**Longest Horizontal Distance Between Mounting Centers:**

Between 0.771 inches and 0.791 inches

**Longest Vertical Distance Between Mounting Centers:**

Between 0.771 inches and 0.791 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Unthreaded hole

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

100.00 feet per second

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Quick disconnect, male

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Type:**

External actuation point screw

**Contact Stimulus Rating:**

30.00 differential point inches of water

**Contact Voltage Rating In Volts:**

30.0 dc at sea level third voltage

**Pressure Connector Type:**

Barbed, unthreaded external all connections

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Contacts and terminal surfaces gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0