

View Online at <https://aerobasegroup.com/nsn/5930-01-295-2265>

Outside Diameter:

0.200 inches all connections

Unthreaded Mounting Hole Diameter:

Between 0.101 inches and 0.107 inches

Longest Horizontal Distance Between Mounting Centers:

Between 0.771 inches and 0.791 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.771 inches and 0.791 inches

Pressure Switch Type:

Differential

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

100.00 feet per second

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Quick disconnect, male

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

30.00 differential point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Pressure Connector Type:

Barbed, unthreaded external all connections

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts and terminal surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0