

View Online at <https://aerobasegroup.com/nsn/5930-01-295-2276>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.440 inches

Overall Height:

Between 1.070 inches and 1.090 inches

Overall Width:

Between 1.070 inches and 1.090 inches

Body Width:

Between 1.070 inches and 1.090 inches

Body Height:

Between 1.070 inches and 1.090 inches

Case Material:

Metal

Actuator Length:

Between 0.800 inches and 0.820 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.260 inches and 0.280 inches

Actuator Width:

Between 0.800 inches and 0.820 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Green single actuator and natural single actuator

Actuator Inscription:

Air ready single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

3.160 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and full display lens

Nonpile-up Contact Arrangement:

1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc and 1.000 amperes resistive ac and 0.500 amperes inductive ac

Special Features:

Full display lens

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0