## NSN 5930-01-295-2871

Push Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-295-2871  |
|--|
| Body Style:  |
| Panel mounted  |
| Hazardous Locations/environmental Protection:  |
| Moisture resistant   |
| Body Width:  |
| 0.688 inches   |
| Body Height:   |
| 0.688 inches   |
| Actuator Length:   |
| 0.620 inches   |
| Actuator Style:  |
| Rectangular  |
| Actuator Height:   |
| 0.120 inches   |
| Actuator Width:  |
| 0.620 inches   |
| Actuator Color:  |
| Black single actuator and black single actuator and black single actuator and black single actuator                                  |
| Illuminated Actuator Color:  |
| Yellow single actuator and yellow single actuator and yellow single actuator and yellow single actuator                              |
| Actuator Inscription:  |
| Dvs, scns/att, inu single actuator   |
| Maximum Voltage Rating In Volts:   |
| 115.0 ac and 28.0 dc   |
| Mounting Surface To Terminal End Distance:   |
| 2.680 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Nonpile-up Contact Arrangement:  |
| 4 pole, double throw, one position momentary single switch unit  |
| Contact Load Current Rating At Maximum Rated Voltage:  |
| 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes |
| inductive ac and 2.000 amperes lamp ac   |
| Special Features:  |
| Horizontally and vertically split screen   |
| Precious Material And Location:  |
| Contacts silver  |
| Terminal Type And Quantity:  |
| 5 tab, solder lug and 12 turret  |

N/a

Shelf Life:

## NSN 5930-01-295-2871

Push Switch - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

No

Fiig:

A053a0