NSN 5930-01-295-2871

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-295-2871
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Moisture resistant
Body Width:
0.688 inches
Body Height:
0.688 inches
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.120 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator and black single actuator and black single actuator
Illuminated Actuator Color:
Yellow single actuator and yellow single actuator and yellow single actuator and yellow single actuator
Actuator Inscription:
Dvs, scns/att, inu single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.680 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes
inductive ac and 2.000 amperes lamp ac
Special Features:
Horizontally and vertically split screen
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
5 tab, solder lug and 12 turret

N/a

Shelf Life:

NSN 5930-01-295-2871

Push Switch - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A053a0