

View Online at <https://aerobasegroup.com/nsn/5930-01-295-2880>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Explosion proof and humidity resistant

**Overall Length:**

3.440 inches

**Overall Height:**

Between 1.070 inches and 1.090 inches

**Overall Width:**

Between 1.070 inches and 1.090 inches

**Body Width:**

Between 1.070 inches and 1.090 inches

**Body Height:**

Between 1.070 inches and 1.090 inches

**Case Material:**

Metal

**Actuator Length:**

Between 0.800 inches and 0.820 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.260 inches and 0.280 inches

**Actuator Width:**

Between 0.800 inches and 0.820 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Green single actuator and natural single actuator

**Actuator Inscription:**

Radiate single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

3.160 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal and full display lens

**Nonpile-up Contact Arrangement:**

1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc and 1.000 amperes resistive ac and 0.500 amperes inductive ac

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

1 socket, integrated wire termination

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0