NSN 5930-01-295-3367

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-295-3367

Body Style: Panel mounted Hazardous Locations/environmental Protection: Explosion proof and humidity resistant **Overall Length:** 3.440 inches **Overall Height:** Between 1.070 inches and 1.090 inches **Overall Width:** Between 1.070 inches and 1.090 inches **Body Width:** Between 1.070 inches and 1.090 inches **Body Height:** Between 1.070 inches and 1.090 inches **Case Material:** Metal Actuator Length: Between 0.800 inches and 0.820 inches **Actuator Style:** Rectangular **Actuator Height:** Between 0.260 inches and 0.280 inches Actuator Width: Between 0.800 inches and 0.820 inches **Actuator Color:** White single actuator **Illuminated Actuator Color:** White single actuator **Actuator Inscription:** Fault reset single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Mounting Surface To Terminal End Distance: 3.160 inches Inclosure Type: Fully enclosed **Mounting Method:** Panel **Features Provided:** Actuator seal and full display lens

Nonpile-up Contact Arrangement:

1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

NSN 5930-01-295-3367

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc and 1.000 amperes resistive ac and 0.500 amperes inductive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0