

View Online at <https://aerobasegroup.com/nsn/5930-01-295-7468>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

1.100 inches

Overall Height:

2.760 inches

Overall Width:

0.930 inches

Bushing Length:

0.470 inches

Body Length:

1.100 inches

Body Width:

0.930 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

4920-01-134-4473 test set inertial navigation system

Mounting Surface To Terminal End Distance:

1.150 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

6 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

18 turret

Specification Data:

81349-mil-s-8805/98 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0