

View Online at <https://aerobasegroup.com/nsn/5930-01-295-8498>

Thread Class:

2b

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.375 inches

Overall Height:

Between 0.860 inches and 0.900 inches

Overall Width:

Between 0.860 inches and 0.900 inches

Body Diameter:

0.562 inches

Bushing Length:

Between 0.296 inches and 0.328 inches

Actuator Diameter:

Between 0.370 inches and 0.377 inches

Actuator Height:

0.250 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0