

View Online at <https://aerobasegroup.com/nsn/5930-01-295-8498>

**Thread Class:**

2b

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

1.375 inches

**Overall Height:**

Between 0.860 inches and 0.900 inches

**Overall Width:**

Between 0.860 inches and 0.900 inches

**Body Diameter:**

0.562 inches

**Bushing Length:**

Between 0.296 inches and 0.328 inches

**Actuator Diameter:**

Between 0.370 inches and 0.377 inches

**Actuator Height:**

0.250 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0