

View Online at <https://aerobasegroup.com/nsn/5930-01-296-2205>

Thread Class:

2a all threaded stud

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.250 inches

Overall Height:

3.000 inches

Overall Width:

3.188 inches

Body Length:

3.000 inches

Longest Horizontal Distance Between Mounting Centers:

2.625 inches

Longest Vertical Distance Between Mounting Centers:

2.438 inches

Pressure Switch Type:

Gage

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Decrease

Proof Pressure:

1000.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

50.0 milliamperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+10.00/+223.00 actuation point pounds per square inch gage and +12.00/+250.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point hex nut with scale and internal deactuation point hex nut with scale

Contact Voltage Rating In Volts:

600.0 ac at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0