

View Online at <https://aerobasegroup.com/nsn/5930-01-296-2208>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Watertight and dustproof

**Overall Length:**

5.219 inches

**Overall Height:**

5.031 inches

**Overall Width:**

2.812 inches

**Body Height:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.656 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

216.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 two circuit, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes motor load third voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+10.00/+180.00 actuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

550.0 dc at sea level fourth voltage

**Pressure Connector Type:**

Flare, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Thread Series Designator:**

Ptf-sae short single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0